

How to Care for Your Sealed Parquet Flooring

Material Characteristics

Sealed parquet combines the natural look of wood with a durable protective layer. The closed surface reliably protects the wood against wear and dirt and ensures easy maintenance in everyday use.

As a natural product, wood reacts to changes in indoor climate. Minor shrinkage in dry conditions or slight swelling with increased humidity is typical and not a quality defect.

Indoor Climate

Recommended indoor conditions are 20 to 22 degrees Celsius with 40 to 50 percent relative humidity. Humidity should not fall below 35 percent. On heated constructions, the surface temperature must not exceed 26 degrees Celsius.

Initial Treatment After Installation

After installation, we recommend an initial treatment with a suitable polish to additionally protect joints and optimally seal the surface.

Regular Cleaning

Vacuum with a hard floor nozzle or dry mop. Clean with a slightly damp cloth. If necessary, use a neutral cleaning agent. Remove shoe marks with a mild cleaner.

Recommended

- *Dirt trap mats*
- *Felt pads*
- *Suitable parquet chair castors*
- *Regular refreshing with parquet polish*

Avoid

- *Abrasive cleaners*
- *Steam cleaners*
- *Wet cleaning*
- *Cleaning machines*
- *Carpet underlays containing plasticizers*

General Information

These recommendations reflect the current state of cleaning technology. No liability is assumed in individual cases.

Slip resistance is significantly influenced by care and cleaning.

We are happy to advise you personally and provide the care products precisely matched to your floor at Teppich & Parkett CC AG.

More Care Tips

